

Komitet Mechaniki Polskiej Akademii Nauk

Politechnika Rzeszowska
im. Ignacego Łukasiewicza

Instytut Podstawowych Problemów Techniki
Polskiej Akademii Nauk

III KRAJOWA KONFERENCJA

NANO- i MIKROMECHANIKI



ORGANIZATORZY:



POLITECHNIKA
RZESZOWSKA
im. IGNACEGO ŁUKASIEWICZA



ISBN 978-83-89687-739

KKNM 2012

IPPT PAN, WARSZAWA 2012

Komitet Mechaniki Polskiej Akademii Nauk
Instytut Podstawowych Problemów Techniki
Polskiej Akademii Nauk
Politechnika Rzeszowska
im. Ignacego Łukasiewicza

III National Conference of Nano and Micromechanics

Under the auspices of the Ministry of Science and Higher Education
Prof. Barbara Kudrycka

III Krajowa Konferencja Nano i Mikromechaniki

Pod patronatem Ministra Nauki i Szkolnictwa Wyższego
Prof. Barbary Kudryckiej

4–6 July 2012
IPPT PAN, Warszawa

Piotr M. Korczyk^a, Sławomir Jakielka^b, Ładislav Žíši^b, Piotr Garstek^b

MICROFLUIDIC TRAP SYSTEMS FOR PRECISE OPERATIONS ON DROPLETS

^a*Institute of Fundamental Technological Research, Polish Academy of Sciences,
ul. Pawińskiego 5B, 02-106 Warsaw (Poland)*

^b*Institute of Physical Chemistry, Polish Academy of Sciences,
ul. Kasprzaka 44/52, 01-224 Warsaw (Poland)*

E-mail: piotr.korczyk@ippt.gov.pl, garst@ichf.edu.pl

Keywords: droplets, microfluidics

Techniques operating on droplets and treating them as single reactors are very promising due to their advantages: i) lack of dispersion, ii) fast mixing, iii) superior control on kinetics of reactions, iv) easy to parallelization v) small volume¹. The challenge is to control the size and content of each droplet simultaneously.

We present concept of microfluidic modules that taking advantage of the capillary back-pressure, allow to trap, dose and realize precise portion of liquid. The precision is encrypted in the geometry of the device and a large mismatch of shear stresses and capillary forces. This mismatch guarantees reproducibility over a wide range of rates of flow that need not be controlled precisely. We also demonstrate that these modules allow to build systems that perform complicated protocols precisely while not precise control.




Fig. 1: Example of metering trap. a) – filling the trap by the flow of long droplet, b) – droplet passing the filled trap.

REFERENCES

- [1] H. Song, D. L. Chen, and R. F. Ismagilov, *Angewandte Chemie International Edition*, 2006, **45**, 7336–7356.